## **AMENDMENTS TO THE CLAIMS**

This listing of claims will replace all prior versions and listings of claims in the application:

## **LISTING OF CLAIMS:**

- 1. (Currently amended)Facility for an end customer for generating a connection between a telecommunications network of a network operator and an in-house power supply network of the end customer for rendering possible the transmission of, telecommunications signals (POTS; ISDN; DSL) via the in-house power supply network of the end customer, telecommunications signals (POTS; ISDN; DSL) to be reproduced by the end customer.
- 2. (Original)Facility according to claim 1, wherein the facility comprises a filter for forwarding telecommunications signals (POTS; ISDN; DSL) and for blocking direct-current signals and the filter is connected between the telecommunications network and the in-house power supply network.
- 3. (Original)Facility according to claim 1, wherein the facility comprises a filter for blocking telecommunications signals (POTS; ISDN; DSL) and for forwarding alternating-current signals and the filter is connected between the in-house power supply network of the end customer and a power supply network of a power network operator.

2

AMENDMENT UNDER 37 C.F.R. § 1.111 U.S. Appln. No. 10/023,806

- 4. (Original)Facility according to claim 2, wherein the filter is a high-pass filter with a limiting frequency in the range from 50 Hz to 70 Hz, or a bandpass filter with a lower limiting frequency in the range from 50 Hz to 70 Hz.
- 5. (Original)Facility according to claim 3, wherein the filter is a low-pass filter with a limiting frequency in the range from 50 Hz to 70 Hz, or a bandpass filter with an upper limiting frequency in the range from 50 Hz to 70 Hz.
- 6. (Original)Facility according to claim 1, wherein the facility is designed as a power meter or fuse box with an interface to the telecommunications network or as a network termination or telecommunications exchange with a telecommunications interface to the in-house power supply network of the end customer.
- 7. (Currently amended)Local, in-house power supply network of an end customer, comprising a facility for generating a connection between a telecommunications network of a network operator and the in-house power supply network of the end customer, for rendering possible the transmission of, telecommunications signals (POTS; ISDN; DSL) via the in-house power supply network of the end customer, telecommunications signals (POTS; ISDN; DSL) to be reproduced by the end customer.

AMENDMENT UNDER 37 C.F.R. § 1.111 U.S. Appln. No. 10/023,806

- 8. (Currently amended)Method for the transmission of telecommunications signals, in which telecommunications signals (POTS; ISDN; DSL) received from a telecommunications network of a network operator and to be reproduced by an end customer are forwarded via a local, in-house power supply network of an-the end customer.
- 9. (Original)Method according to Claim 8, wherein direct-current signals received from the telecommunications network of the network operator are not forwarded via the local, in-house power supply network of the end customer.
- 10. (Original)Method according to Claim 8, wherein telecommunications signals (POTS; ISDN; DSL) received from the local, in-house power supply network of the end customer are fed into the telecommunications network of the network operator.

4